


Standard 'Designer' grates

'Designer' grates are available in 50mm, 100mm, 200mm and 300mm nominal widths compatible with ACO channels.



Galvanised Intercept



Available in 100, 200, 300mm widths
Slip rated to AS 4586: P3; R10




Iron Intercept



Available in 50, 100, 200, 300mm widths
Slip rated to AS 4586: P2; R10/R9¹




Iron Wave



Available in 100, 200, 300mm widths
Slip rated to AS 4586: P4; R10




Galvanised Longitudinal



Available in 100mm width only
Slip rated to AS 4586




Plastic Black Intercept



Available in 100mm width only
Slip rated to AS 4586: P4; C/B¹; R9/R10¹




Plastic Grey Intercept



Available in 100mm width only
Slip rated to AS 4586: P4; C/B¹; R9/R10¹



Plastic Slotted



Available in 100mm width only
Slip rated to AS 4586: P5; B/C¹; R11/R10¹



Stainless 5 Star



Available in 50, 100, 200, 300mm widths
Slip rated to AS 4586: P4; C; R11
Also available in R12
(See Page 11 for more variations)



Stainless Wedgewire



Available in 100, 200, 300mm widths
Slip rated to AS 4586: P3; C/B¹; R10
(See Page 11 for more variations)



¹ Test direction (perpendicular/parallel) relative to the grate's length